



CAUTION 500 VOLTS AVAILABLE DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS FOR BLEEDERS TO DISSIPATE B+ VOLTAGE

FENDER MUSICAL INSTRUMENTS
 CBS MUSICAL INSTRUMENTS
 A DIVISION OF CBS INC.
 FULLERTON, CALIFORNIA
 U.S.A.

TEST DATA

(MV) DENOTES TYPICAL 1K HZ SIGNAL FOR 10 WATT OUTPUT (WITH PLUS INTO INPUT JACK) (USE 0.1 MFD 600 CAPACITOR IN SERIES WITH GENERATOR'S "HOT" LEAD)
 CONTROL SETTINGS - EQUALIZERS AT MID POSITION
 PRESENCE AT MINIMUM
 OTHERS AT MAXIMUM

D.C. VOLTAGES READ WITH NO SIGNAL INPUT

1. USED IN SOME PLACES
 2. ALL RESISTORS 1/2 W. 10%
 ALL CAPACITORS AT LEAST 100 P.P.M.
 NOTES: UNLESS OTHERWISE SPECIFIED

SAMPLES OF FIRST ARTICLE PARTS MUST BE APPROVED BY FENDER, ROGERS, RHODES R & D ENG. BEFORE STARTING PRODUCTION

HEAT TREATMENT	UNLESS OTHERWISE SPECIFIED TOLERANCES	DWN	DATE
FRACTIONS	± 1/32	CHK	
JX	± 0.10	APPD	
JXK	± 0.05	ILL	
ANGLES	± 1/2°	APPD	
FRAC. ON WOOD	± 1/16	E.E.	
HOLE S. CORED	± .005 - .000		
BEND ANGLES	± 1°		
HOLES - DRILLED & PIERCED	± .002 - .001		
SPRT ANGLES	MAX.		
STRAIGHTENING	MAX.		
UNMARKED ANGLES ARE 90°			
UNLESS OTHERWISE SPECIFIED			

Fender/Rogers/Rhodes
 CBS MUSICAL INSTRUMENTS - A DIVISION OF CBS INC.
 FULLERTON, CALIFORNIA 92701
 PART NAME: SCHEMATIC - 200 WATT BASS AMPLIFIER W/LED
 RELEASE DATE: 1/68
 SCALE: 1" = 1"

ALTERNATE PRIMARY CONNECTIONS FOR 210/250V 50/60 HZ. REMOVE .047-1R5 WCG GROUNDING SWITCH ACCESSORY OUTLET AND USE 3A 250V FUSE AND A.C. CORD 013002